VIVANT VLeaf Go User Manual

Package Includes

VLEAF GO

USB Cable

Cleaning Brush

Packing Tool

Package Includes

Silicone Mouthpiece Cover

Air Cooler

O Ring (For Chamber)

O Rings (For Scoop)

Chamber

Scoop Seal

Mesh

Mesh Ring

Getting Started

1. Pull out the top cap.

2. Grind your material.

Material

3. Use the scoop to load your material.

Getting Started

4. Use the cap to pack down your material.



5. Cap it.

Getting Started

6. Press the fire button 5 times to power on/off.

7. Instant Mode: Press and hold the fire button to vape. Doing several consecutive puffs leading to a longer inhalation when the device is cold may help extract vapor faster. Inhaling for 10-20 seconds (while holding the fire button) produces good extraction.

Selecting Temp.

Press the fire button 2 times to select between low(green), medium (yellow), and high (red) temperatures.



LED Display

The LED light indicates both your temperature levels and battery levels.

Temperature Levels

LOW

GREEN

MEDIUM

YELLOW

HIGH

RED

LED Display

Quickly press the fire button 1 time to check the battery level.

Battery Levels

Full: Constant green light

GREEN

Medium: Yellow light flashes slowly.

YELLOW

Low: Red light flashes quickly.

RED

Session Mode

Session Mode: Press the fire button 3 times to start session mode where the device stays on for 30 seconds without the need to hold down the button (quickly press the fire button 1 time to turn off session mode).

Attaching Waterpipe

To vaporize through water simply remove the silicone mouthpiece cover and insert the cap into the down stem of your waterpipe as shown below:



Cleaning



1. Remove the rest vaporized flower using the extended section of the cap. If needed use the cleaning brush to remove any residue.

2. Remove the scoop assembly by twisting it counterclockwise. Disassemble the scoop by taking out the chamber and seals.

Remove air cooler and mesh screen from the mouthpiece.

Cleaning

3. Soak parts in 50% isopropyl alcohol for 10-20 minutes.

4. Rinse the scoop assembly with water and dry off. Install the scoop assembly by twisting it clockwise until it clicks into place.